

NATIONAL-SPENCER, INC.

ZEE LINE LUBRICATION EQUIPMENT

Phone 800-231-1525

Fax 800-637-9511

Web Address www.zeeline.com

Part # 1212A

Air Operated Chassis Lube System

Features

- ❖ Heavy-duty 55:1 ratio
- ❖ Air pressure 70-100 PSI
- ❖ Air consumption 5.5 CFM
- ❖ Air inlet ¼" NPT
- ❖ Grease outlet ¼" NPT
- ❖ Fits 400 lb. drum
- ❖ Connecting hoses (1804/2004)
- ❖ Tube length 36 5/8"
- ❖ Drum adapter 2" NPT 1 5/32" tall
- ❖ Pump tube diameter 1 5/32"
- ❖ ¼" x 48" grease hose
- ❖ ¼" x 48" air hose
- ❖ Foot valve
- ❖ Air filter with auto water drain, regulator, gauge, ball valve and quick disconnects (1559A-ASSY)
- ❖ Bung adapter
- ❖ Approximate capacity
2.2 lbs./min free flow with 100 psi air pressure and grease at 68° F
1.3 lbs./min through 33 feet of ¼" hose and grease control handle

Recommended for

- ✓ Greases through NLGI #2

Application

- Automotive
- Industrial
- Agriculture

Number of boxes and contents

- Pump in 1 box (51" x 10" x 7") (21 lb.)
Cover in 1 box (26" x 25" x 2") (20 lb.)
- UPC Code 0 1595441229 8

Pump with drum
cover and follower
plate for pumping
grease from 400-lb.
drum



Regulator
Combination
Unit
1559A-ASSY



Drum Cover
18525



Follower Plate
18573



High Pressure
Grease Hose
1804



Air Hose 2004

**1212AAR is the pump ONLY
and no accessories**